

	Amendment	Date
R0	First issue	18/12/15
R2	Second issue	01/11/21

## V-CUT BOARD SPECIFICATION OUTLINES

### 1xx METAL STUD LINING SYSTEM WITH V-CUT RECESSED SKIRTING WALL TYPE xx

- Manufacturer:
  - Boards: V-Cut Ltd, Unit 8 Dundas Close, Posmouth, PO3 5RB  
Tel: +44 (0)20 3092 1377  
[enquiry@vcut.co.uk](mailto:enquiry@vcut.co.uk). Web: [www.vcut.co.uk](http://www.vcut.co.uk) or similar approved.
  - Product reference: V-Cut KU Skirting Boards.
  - Framing: British Gypsum Ltd, East Leake, Loughborough, Leicestershire LE12 6JT Tel: 0870 545 6123 Fax: 0870 545 6356 Email: [BGTechnical.Enquiries@bpb.com](mailto:BGTechnical.Enquiries@bpb.com) Web: [www.british-gypsum.com](http://www.british-gypsum.com) or similar approved.
  - Plasterboards: Knauf/British Gypsum/Siniat [delete as required] or equal approved
- Studs:
  - Type: 48mm Gypframe 48 S 50 'C' Studs or similar [size according to manufacturer's guidelines].
  - Centres: generally 600mm [or as required according to the manufacturer's guidelines].
- Head & floor track:
  - Type: 50mm Gypframe 50 FEC 50 'U' tracks or similar [size according to manufacturer's guidelines].
- Insulation: Not required [*amend if required*].
  - Thickness:-.
- Linings: 2 x 12.5mm plasterboards with outer being V-Cut type KU machined board including 12.5mm factory glued v cut return on one short edge of the board with continuous paper face to form recess into wall fixed with drywall screws and set xx mm [*fill in as required*] above the top of the skirting board to form a shadow recess. This edge does not need to be trimmed.
- Finishing: Joints taped and jointed as manufacturer's recommendations.
  - Primer/ Sealer: Primer to painted areas.
  - Accessories: Skirting board.
- Skirting: Timber/MDF recessed skirting to align with outer plasterboard to form flush wall appearance
  - Manufacturer: [*fill in as required*]
  - Finish: [*fill in as required*]
  - Height: [*fill in as required*]
- Other requirements:-.