

# Plasterboard innovation!

Formed to virtually any angle or curve, fixed and finished as standard plasterboard, giving perfect results - every time!

## Features

- ▼ Quick and easy
- ▼ No cutting
- ▼ Reduces waste
- ▼ Excellent finish

## Applications

- ▼ Shop fit-outs
- ▼ Shopping centres
- ▼ Galleries
- ▼ Museums
- ▼ Office fit-outs
- ▼ Foyers and receptions
- ▼ Hotels
- ▼ Airports
- ▼ Stadiums



L profile



U profile



Z profile



Complex profile



Curved profile




## Flexibility and simplicity

We groove standard and custom sheets of plasterboard, using CNC equipment, creating flexible boards able to accommodate straight and curved profiles in walls, column linings, ceiling bulkheads, or for end terminations to partition walls.







## Standard L profiles



### Benefits

- ▼ Fantastic design opportunities
- ▼ Tight folding options
- ▼ Precise manufacture
- ▼ Clean and sharp edge finish
- ▼ High stability and strength
- ▼ No cutting of boards on site
- ▼ No corner/trimming beads
- ▼ Reduced jointing on site
- ▼ Reduced requirements for framing
- ▼ More economical than moulded profiles
- ▼ Easier to repair than beaded constructions
- ▼ Custom profiles available

	Requirement	Permissible	Comment
	Folding boards	✓	Paper faced boards only – straight
	Cut/machined boards	✓	All types. L/U shaped boards to curve, supplied either preglued or in parts
	Board thicknesses	up to 25mm	
	Standard boards	✓	
	Fire resistant boards	✓	Follow manufacturer's printed literature for achieving specific fire rating requirement
	Sound resistant boards	✓	Follow manufacturer's printed literature for achieving specific sound rating requirement
	Moisture resistant boards	✓	
	Vapour boards	✗	Request technical support
	Impact resistant boards	✓	Follow manufacturer's printed literature for achieving specific impact resistance requirement
	Thermal insulation boards	✗	Request technical support
	Pre-perforated boards	✗	Not recommended for V cutting
	Square edged	✓	
	Tapered edged	✓	
	Rounded edged	✓	
	Installation conditions		Follow board manufacturer's printed literature
	Machining accuracy		1/10th of a millimetre
	Maximum board width	1250mm	
	Maximum board length	3000mm	
	Final finish requirements		For tape and joint, skim or decoration - follow board manufacturer's printed literature

Note: This brochure illustrates a number of standard solutions. However, V-Cut plasterboard profiles have many more applications and we welcome the opportunity to discuss your individual and bespoke solutions.

Your nearest stockist



tel: +44(0) 8450 585869  
email: info@vcut.co.uk  
www.vcut.co.uk